



NPT TAP 3/4"
 "Flush to "2Turn large"
 or M25 P1.5, 6H
 Threaded engaged
 or M20 P1.5, 6H
 Threaded engaged

⊕ M4 EARTH BOLT
 Earth Point
 - WRENCH BOLT : M4*6, SUS 304
 - CONECT TERMINAL :
 I.D ∅4.2, O-TYPE, MAT'L C5212
 - EARTH LINE : Above 4mm²

Model No.	LZ1710 - AL
Material	Head, Body & Cover Die cast Bs Bolt, Nut & Ect - SUS
Contact	2KCT-DB, 1A1B, 125VAC 10A, 250VAC 6A 125VDC 0.8A & 250VDC 0.4A
Insulation Resistance	100MΩ Min. At 500V DC
Protection Grade	Explosion Proof : Ex db IIC T6 Gb Tamb : -55° C ~ 40° C
Cable Entry	NPT 3/4 or M25 or M20
Color	Maker standard
Surface resistance of the material	Below 1GΩ at (50±5)% relative humidity
Gross surface area of painted	Max. 40,000 mm ²

1	LZ1710-S005	LZ1710-W	Bs & ect	1	-
Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
Y.H.JANG	-	ZZANGA	-	3	OCT. 10. 2019
TITLE					SCALE
W TYPE OUT DWG.					1/1
SYE.C For Marine, Heavy Duty & Exp. L/S LZ1710					
DWG. Nr.				EDITION	SHEET
LZ1710-S005				1	1/1